

BluOcean™ USB GSM Modem

BluOcean™ popular range of World-class standard GSM and GPRS modems are widely used by corporations and software houses across the world. To ensure quality and speed maximization, only top quality chipset from Siemens™ is used in the BluOcean™ modems.



SIEMENS



Complies with
IDA Standards
DB103815



Technical Specification

- SIM card holder integrated
- 3V SIM Interface
- Activity Status LED Indication
- Power Output: Class4 (2W @ EGSM 900/GSM 850)
Class1 (1W @ GSM 1800/1900)
- Normal operation temperature: -20 to 55°C
- Operating Voltage : 5 to 24VDC
- Typical idle mode supply current: 5mA
- Baud rates: 300-9600 bits/s
- Compliant with ETSI GSM Phase 2 +
- Control via AT commands (GSM07.07 & 07.05)

Design

- USB Interface
- Silvery Grey Color With Metal Casing
- Weight 100g With Dimension 98x54x25mm

SMS Specification

- Text and PDU mode
- Cell broadcast
- Point to Point MO and MT

Fax Specification

- Group 3 (Class 1,2)

Supported Operating System

- Windows 2000, NT, XP, Vista, 7, Linux (Redhat 7.3/ 8.0/ 9.0), Mac OS X

Included Accessories



USB Extension Cable



Antenna

Type	Frequency	Coverage	Model
Dual Band	GSM 900/1800 MHz	Asia & Europe	Siemen-U-A4

Siemens Embedded

Directly connect to computer. Easily plug and play. Ideal for all users!